

DrainMat is the ideal solution to protect entrances from water and debris. DrainMat can be used for residential and commercial use to protect from rain, snow, sand, and everyday debris. Suitable for pedestrian traffic only.

- Reduces transfer of dirt and water into the home or building
- Discreet drainage solution for entrance areas
- Indoor version holds dust and debris and prevents spread around the home

Suitable applications:

- Residential doorways
- Mud room
- Outdoor showers
- Commercial entrances



Base options



MatFrame Aluminum frame for indoor mat use - small or large



Polymer concrete base with 4" schedule 40 outlet - small



Plastic base with 4" schedule 35 outlet - small only



Polymer concrete base with 4" schedule 40 outlet - large

www.acomarkant.com

Mat options



Aluminum & rubber mat



Galvanized mesh mat



Stainless wedge-wire mat



Part Table

	Part No.	Length inches	Width inches	Height inches	Wgt. lbs
Bases					
Small					
Polymer concrete	00398	23.62	15.75	3.15	26.4
Plastic	82400	23.62	15.75	3.15	3.1
Indoor MatFrame	01995	23.62	15.75	1.00	2.0
Large					
Polymer concrete	00400	39.37	19.69	3.15	49.7
Indoor MatFrame	01997	39.37	19.69	1.00	2.4
Mats					
Small					
Galv. steel	01207	23.62	15.75	0.79	8.8
Aluminum/rubber	01213	23.62	15.75	0.79	7.7
Stainless	97972	23.62	15.75	0.79	17.6
Large					
Galv. steel	01209	39.37	19.69	0.79	18.9
Aluminum/rubber	01215	39.37	19.69	0.79	13.7
Stainless	97975	39.37	19.69	0.79	36.7

Installation Instructions

Outdoor DrainMat



1 Excavate area large enough to fit DrainMat base, add 2" sand, compact well.



2 Install pipework.



3 Level base unit. Backfill surround with concrete and finish surface as desired (tile, paver, etc.).



4 Ensure finished surface is 1/8" higher than the DrainMat to assist water drainage. Fit mat into finished installation.

Indoor MatFrame



1 Measure area where MatFrame will be placed indoors.



2 Excavate area large enough to fit DrainMat base.



3 Install MatFrame, tile floor ensuring surface is 1/8" higher than MatFrame to prevent trip hazard.



4 Install mat and installation is complete.

ACO Polymer Products, Inc.

East Sales Office

P.O. Box 245
Chardon, OH 44024
Tel: (440) 285-7000
Toll free: (800) 543-4764
Fax: (440) 285-7005

West Sales Office

P.O. Box 12067
Casa Grande, AZ 85130
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Electronic Contact

info@acomarkant.com
www.acomarkant.com

Follow us on

